

P23 AL-UV (Aluminium UV Reflective – Silver in Colour)

The product was developed as a protective solution for the waterproofing industry and offers excellent bonding properties to bituminous surfaces, timber, metal and cement-based substrates.

Product features include excellent UV protection, bonding properties and waterproofing qualities. Added advantages include high degree of durability and retained flexibility.

PRODUCT USES

- ✓ As a Top Coat.
- ✓ Steel roof;
- ✓ Steel poles;
- ✓ Fences.

ADVANTAGES

- ✓ Full waterproofing and bonding properties.
- ✓ Adheres well to a variety of surfaces.
- ✓ Suitable for vertical & horizontal surfaces.
- ✓ Quick and easy to apply.
- ✓ When applied, the product undergoes a chemical reaction that helps prevent "wash-away" when rain occurs shortly after application.
- ✓ Has the ideal mix of elasticity vs. strength to withstand robust African climatic conditions.
- ✓ Compatible to bituminous surfaces.
- ✓ Does not harden or go brittle over time.
- ✓ No need for long hours of drying time (depending on the weather & area that is being waterproofed.)
Outdoors (summer) 3hours – indoors 12-18hours.
- ✓ Can work under extreme conditions (-28° up to +65°)
- ✓ Excellent UV protection.

COVERAGE

- ✓ On an average of 6 m² per Liter.

IMPORTANT NOTES & PREPERATION

- ✓ Only use **P23 HAS 100** to clean or mix into product.

APPLICATION

- ✓ Stir or shake tin properly before using.
- ✓ Only use rollers and brushes that can be used with solvent or P23 approved products.
- ✓ Make sure all surfaces are clean and dry, free of dust and loose particles before applying the product.

IMPORTANT! ALLOW TO DRY BETWEEN COATS.

- ✓ After waterproofing with **P23 FLEXI-SEAL** apply two coats of **P23 AL-UV TOP COAT.**

DO NOT APPLY ON A WATER BASED WATERPROOFING OR PAINT.

- ✓ During the maintenance after applying the 2 coats **P23 FLEXI-SEAL** apply 1 coat of **P23 AI-UV TOP COAT.**

IMPORTANT! AFTER USE - KEEP LID TIGHTLY SEALED.