

P23 FLEXI-FIX (Solvent emulsion – Colour to suit)

The **P23 FLEXI-FIX** is a durable & elastic emulsion that has been designed to achieve full waterproofing and bonding properties to steel, pottery (ceramic) cement-based substrates & glass, retaining its plasticity.

P23 FLEXI-FIX protects metal surfaces from rust & is non-toxic when cured (dry). **P23 FLEXI-FIX** allows for the sentimental type to repair their most lovable accessories around the house.

PRODUCT USES

In conjunction with **P23 FLEXI-TEX1100**, **P23 FLEXI-FIX** can be used to Repair:

- ✓ Pots
- ✓ Vases
- ✓ Any decorative item consisting of steel, ceramic & glass.

ADVANTAGES

- ✓ Full waterproofing and bonding properties.
- ✓ Adheres well to a variety of surfaces.
- ✓ Suitable for vertical & horizontal surfaces.
- ✓ Quick and easy to apply.
- ✓ Has the ideal mix of elasticity vs. strength.
- ✓ Does not harden or go brittle over time.

IMPORTANT NOTES & PREPERATION

- ✓ Repair damaged or cracked sections with **P23 BINDING FILLER** and/or **P23 FLEXI-TEX 1100**
- ✓ Only use **P23 HAS 100** to clean or mix into product.

APPLICATION

- ✓ Stir or shake tin properly before using.
- ✓ Only use rollers and brushes that can be used with solvent or P23 approved products.
- ✓ Make sure all surfaces are clean and dry, free of oil dust and loose particles before applying the product.

IMPORTANT! ALOW TO DRY BETWEEN COATS.

- ✓ Apply a generous coat of **P23 FLEXI-PRIME**.
- ✓ Apply **P23 FLEXI-FIX**, followed directly by placement of **P23 FLEXI-TEX 1100** membrane if you require) (size may differ according to area which must be repaired) followed directly by another coat of **P23 FLEXI-FIX**, ensuring complete saturation of the membrane on both side , avoiding wrinkles, bubbles and dry patches.
- ✓ Apply two coats of **P23 FLEXI-FIX**. Allow to dry completely between coats.

IMPORTANT! AFTER USE - KEEP LID TIGHTLY SEALED.